

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
9 June 2005 (09.06.2005)

PCT

(10) International Publication Number
WO 2005/053159 A2

(51) International Patent Classification⁷: **H03K 5/13**

(21) International Application Number:
PCT/EP2004/014912

(22) International Filing Date:
26 November 2004 (26.11.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
03292967.1 28 November 2003 (28.11.2003) EP

(71) Applicant (for all designated States except US):
FREESCALE SEMICONDUCTOR, INC. [US/US];
6501 William Cannon Drive, Austin, TX 78735 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **IHS, Hassan**
[MA/FR]; 8 Rue Robert Aron, Apt 305, F-31100 Toulouse
(FR).

(74) Agent: **WHARMBY, Martin, A.**; Impetus IP Ltd, Grove
House, Lutyens Close, Chineham Court, Basingstoke,
Hampshire RG24 8AG (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **CLOCK PULSE GENERATOR APPARATUS WITH REDUCED JITTER CLOCK PHASE**



(57) **Abstract:** Clock pulse generator apparatus comprising a clock pulse generator (CLK) for generating a train of primary clock pulses having leading and trailing edges. A delay line (14) produces a train of delayed clock pulses (CLK D) presenting delayed edges whose timing relative to corresponding edges of the primary clock pulses (CLK) is defined by the delay line. A logic circuit (15) produces a train of combined clock pulses (CLK JF) presenting leading and trailing edges defined alternately by one of the delayed edges and the corresponding edge of the primary clock pulse, so that the combined clock pulses comprise active clock phases (ACP) having widths defined by the delay line; the variability of the widths of the active clock phases (ACP) is smaller than the variability of the positions of the leading and trailing edges of the primary clock pulses (CLK). The active clock phases (ACP) alternate with non-active clock phases (NACP) whose widths vary as a function of variation in the positions of the primary clock pulses (CLK) and absorb those variations. The delay line (14) comprises a series of cascaded, substantially identical delay elements (16). A temperature and process variation circuit (22) is also described. Application especially to continuous-time sigma-delta converters where a critical integrator (2; 10) integrates a signal over periods of time defined by the widths of the active clock phases (ACP).